BLACKSTONE V-Line Single Section Cabinets

Blackstone's Cabinet V-Line is the perfect solution for organizing and securing your rack-mounted networking equipment.
This cabinet can be wall-mounted and is best used when floor space is at a minimum. The VLine is available in a variety of heights.

Part Number	Solid Panel/Glass Door Cabinets									
	VLINE-6-645	VLINE-6-66	VLINE-9-645	VLINE-9-66	VLINE-12-645	VLINE-12-66	VLINE-15-645	VLINE-15-66	VLINE-18-645	VLINE-18-66
PHYSICAL										
Rack Capacity (in Rack Units)	6U		9U		12U		15U		18U	
Depth	450mm	600mm	450mm	600mm	450mm	600mm	450mm	600mm	450mm	600mm
Unit Dimensions (in) H	14.75	14.75	20.00	20.00	25.15	25.15	31.00	31.00	36.00	36.00
W	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50
D	17.72	23.63	17.72	23.63	17.72	23.63	17.72	23.63	17.72	23.63
Max Rail Depth (in)	14.50	20.50	14.50	20.50	14.50	20.50	14.50	20.50	14.50	20.50
Weight Capacity (kg/ lbs.)	60 / 132									
Material	Cold Rolled Steel (1.2mm) Welded Frame Structure									
Painting / Coating	Electro-static Powder Coating									
Door	Tempered Glass Door - Clear/Reversible									
Interior Rails Mounting	Square unthreaded cage nut opening									
ADDITIONAL FEATURES										
Casters	None included									
Cable Management	Cable punch-outs located at top and bottom panel									
Security	Locks included for door and side panels									
Cooling	2 fans included. Strategically placed ventilation for increased airflow.									
Shelving	Includes 1 set of "L" brackets									
Mounting	Mounting bar included									
Assembly	Assembly required									
COMPLIANCE AND CERTIFICATIONS										
EIA/ECA-310-E	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ROHS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PCI	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
HIPAA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
NEMA Rated Type 1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IP20 Protection Grade	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Shipping										
Shipping Dimensions (in) L	25	25	25	25	28	28	33	33	38	38
W	25	25	25	25	25	25	25	25	25	25
H	9	9	9	9	9	9	9	9	9 / 82	9
Shipping wight /lbs.)	49	57	57	65	65	75	74	86		94

BLACKSTONE V-Line Single Section Cabinets (Perforated)

Blackstone's Cabinet V-Line is the perfect solution for organizing and securing your rack-mounted networking equipment.
This cabinet can be wall-mounted and is best used when floor space is at a minimum. The VLine is available in a variety of heights.

Part Number			Solid Panel/Glass Door Cabinets									
		VLINE-6-645-P	VLINE-6-66-P	VLINE-9-645-P	VLINE-9-66-P	VLINE-12-645-P	VLINE-12-66-P	VLINE-15-645-P	VLINE-15-66-P	VLINE-18-645-P	VLINE-18-66-P
PHYSICAL											
Rack Capacity (in Rack Units)		6U		9U		12U		15U		18U	
Depth		450mm	600mm	450mm	600mm	450mm	600mm	450mm	600mm	450mm	600mm
Unit Dimensions (in)	H	14.75	14.75	20.00	20.00	25.15	25.15	31.00	31.00	36.00	36.00
	W	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50	23.50
	D	17.72	23.63	17.72	23.63	17.72	23.63	17.72	23.63	17.72	23.63
Max Rail Depth (in)		14.50	20.50	14.50	20.50	14.50	20.50	14.50	20.50	14.50	20.50
Weight Capacity (kg/ lbs.)		60 / 132									
Material		Cold Rolled Steel (1.2mm) Welded Frame Structure									
Painting / Coating		Electro-static Powder Coating									
Door		Tempered Glass Door - Clear/Reversible									
Interior Rails Mounting		Square unthreaded cage nut opening									
ADDITIONAL FEATURES											
Casters		None included									
Cable Management		Cable punch-outs located at top and bottom panel									
Security		Locks included for door and side panels									
Cooling		2 fans included. Strategically placed ventilation for increased airflow.									
Shelving		Includes 1 set of "L" brackets									
Mounting		Mounting bar included									
Assembly		Assembly required									
COMPLIANCE AND CERTIFICATIONS											
EIA/ECA-310-E		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ROHS		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CE		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PCI		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
HIPAA		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
NEMA Rated Type 1		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IP20 Protection Grade		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Shipping											
Shipping Dimensions (in)	L	25	25	25	25	28	28	33	33	38	38
	W	25	25	25	25	25	25	25	25	25	25
	H	9	9	9	9	9	9	9	9	9	9
Shipping wight / lbs.)		49	57	57	65	65	75	74	86	82	94