


BLACK-STONE CAT 6 4PAIR OUTDOOR U/UTP

PN://BSCO463UTPPEBL

Product Structure Diagram



Standards

UL Subject 444,ANSI/TIA 568C.2,ANSI/TIA 568.2-D,
ISO / IEC 11801, IEC 61156-5, YD/T1019-2013

PoE compliance: Meets IEEE 802.3af and
IEEE 802.3at for PoE applications

Application

- 100 BASE-Tc
- 100 BASE-TX
- 100VG-AnyLAN
- 1000 BASE-T
- 1000 BASE-TX
- 155 Mbps ATM
- 622 Mbps ATM

Characteristics



Mechanical Characteristics	
Operating Temperature	-20~75°C
Maximum Pulling Force	110N
Minimum Bending Radius	4 X O.D.
Flame Test	PVC: CMX/CM/CMG/CMR LSZH : CPR-B2ca/Cca/Dca/Eca/Fca

Product Structure		
Product Name	CAT 6 4PAIR OUTDOOR U/UTP CABLE	CAT 6 8PAIR OUTDOOR U/UTP CABLE
Conductor	23AWG	23AWG
Number Of Pairs	4	4 x 2
Nominal Conductor Dimension	0.57±0.02mm	0.57±0.02mm
Insulation Material	Solid PE	Solid PE
Nominal Insulation Dimension	1.01±0.06mm	1.34±0. 1.01±0.06mm05mm
Color Code	White & Blue/Blue White & Orange /Orange White & Green/Green White & Brown/Brown	
Separator	Yes	Yes
Outer Jacket Material	PE	PE
Ripcord	Optional	Optional
Nominal Cable Diameter	6.20±0.30mm	(6.20±0.30) X (12.60±0.60) mm


Electrical Charateristics

F (MHz)	Attenuation (dB/100m)	NEXT (dB)	PSNEXT (dB)	Prop. Delay (ns/100m)	ACR-F (dB/100m)	PSACR-F (dB/100m)	Return Loss (dB)
1	2,0	74,3	72,3	570	67,8	64,8	20,0
4	3,8	65,3	63,3	552	55,8	52,8	23,0
8	5,3	60,8	58,8	546,7	49,7	46,7	24,5
10	6,0	59,3	57,3	545,4	47,8	44,8	25,0
16	7,6	56,2	54,2	543	43,7	40,7	25,0
20	8,5	54,8	52,8	542	41,8	38,8	25,0
25	9,5	53,3	51,3	541,2	39,8	36,8	24,3
31,25	10,7	51,9	49,9	540,4	37,9	34,9	23,6
62,5	15,4	47,4	45,4	538,6	31,9	28,9	21,5
100	19,8	44,3	42,3	537,6	27,8	24,8	20,1
200	29,0	39,8	37,8	536,5	21,8	18,8	18,0
250	32,8	38,3	36,3	536,3	19,8	16,8	17,3

Black-stone, Installation cable 4 or 8 pairs

Part number guide configurations

Part number guide example for Black-stone Installation Cable Cat7, SFTP, 4P, LSZH YELLOW



PN://BSC I 4 7 3 SFTP LSZH YL

Cat7, SFTP, 4P, LSZH YELLOW PN://BSCI473SFTPLSZHYL

Additional Information

- All Blackstone Cable has been Tested above the standard.
- 305m (1000 ft.) ALL Packaged Tested.
- POE compliance: Meets IEEE 802.3af and IEEE 802.3at for POE applications.
- Lifetime warranty.

NOTE: Any stock orders placed before May 2024 may be assigned a different part number. We kindly advise you to check with our authorized partner or contact us for further assistance.